

Gazpromneft GL-4 75W-85, 75W-90, 80W-85 and 80W-90

Heavy Duty Automotive Gear Oils



Mechanical transmissions



Good EP properties



Good low temperature performance



Semisynthetic 75W-90



Mineral

Gazpromneft GL-4 oils are high performance, heavy duty gear oils formulated from high quality base oils and an advanced additive system. These lubricants are engineered for automotive heavy-duty transmissions, axles, and final drives where protection against wear and scoring is required. Recommended for use in applications where API GL-4 performance is required.

Applications



- Heavy duty manual transmissions, axles and final drives requiring API GL-4 level performance
- Passenger cars, on highway light and heavy duty trucks, and commercial vehicles
- Off highway industries including: construction, mining, quarrying, and agriculture
- Not applicable for hypoid drive axles

Features	Advantages and Potential Benefits
Excellent anti-wear properties	Reduces wear, preventing failures to extend equipment life and reduces maintenance costs
Reliable share stability	Ensure consistent viscosity throughout fluid service life
Good thermal stability and resistance to high temperature oxidation	Extended gear and bearing life due to minimal deposits
Good low temperature lubrication	Reduced wear at start-up and ease of start-up
Excellent rust and corrosion protection	Preventing corrosion for increased equipment protection and equipment life
Foam control	Smooth and lasting performance in severe service operating conditions

Gazpromneft GL-4 80W-85, 80W-90

Approvals

- ZF TE-ML 17A
- ZF TE-ML 16A, 19A (only for SAE 80W-90)
- AVTOVAZ

Meet the requirements/Recommendations

- API GL-4
- ZF TE-ML 08

Gazpromneft GL-4 75W-85, 75W-90

Approvals

- AVTOVAZ (only for SAE 75W-85)

Recommendations

- API GL-4

Typical Characteristics

Properties	Method	Gazpromneft GL-4			
		75W-85	75W-90	80W-85	80W-90
SAE Viscosity Grade	SAE J306	75W-85	75W-90	80W-85	80W-90
Kinematic Viscosity @100°C, mm²/s	ASTM D445	12,8	15,4	12,5	14,5
Brookfield @ -26°C, mPa·s	ASTM D2983		-	147 000	147 000
Brookfield @ -40°C, mPa·s	ASTM D2983	90 000	145 000	-	-
Flash Point (COC), °C	ASTM D92	216	218	224	232
Pour Point, °C	ASTM D97	-42	-42	-29	-30
Density @15°C, kg/m³	ASTM D4052	863	859	894	897
Tribological characteristics, Four-Ball Method					
Load-wear index, N	ASTM D2783	623	575	560	575
Weld point, N		5204	3920	3479	3920

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.