



# Gazpromneft GL-5 75W-90

Automotive gear oil



Mechanical transmissions



Drive axles



High EP properties



Semisynthetic

Gazpromneft GL-5 75W-90 is high performance gear oil designed for transmission components used in both onhighway and off-highway applications. It is formulated from high quality base oils and an advanced additive package to provide excellent shifting performance, good low temperature fluidity, and high temperature viscosity retention.

## **Applications**



























- · Off-highway industries including: construction, mining, quarrying, and agriculture
- Heavy duty axles and final drives requiring API GL-5 level performance
- Constant mesh and steel synchro-mesh manual gearboxes
- Transfer gearboxes and power take-offs

Features	Advantages and Potential Benefits	
Robust EP performance	Protection from gear scuffing and wear	
Reliable share stability	Ensure consistent viscosity throughout fluid service life	
Thermal and oxidation stability	Reducing oil thickening, sludge, and varnish formation due to high operation temperatures to assure extended gear life	
Low temperature fluidity	Wear protection during cold starts	
Protection against corrosion	Preventing corrosion for increased equipment protection and equipment life	

# Recommendations

- API GL-5
- MIL-L-2105D

#### **Typical Characteristics**

Properties	Method	Gazpromneft GL-5 75W-90
SAE Viscosity Grade	SAE J306	75W-90
Kinematic Viscosity @100°C, mm <sup>2</sup> /s	ASTM D445	15,8
Brookfield @-40°C, mPa·s	ASTM D2983	113 000
Flash Point (COC), °C	ASTM D92	200
Pour Point, °C	ASTM D97	- 42
Density @15°C, kg/m³	ASTM D4052	858
Tribological characteristics, Four-Ball Method:		
Load-wear index, N	ASTM D2783	662
Weld point, N		4900

### **Health, Safety & Environment**

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.

our technical helpdesk. E-mail: OilSupport@gazprom-neft.ru 05/2020

may occur. The information contained is subject to change without notice. Gazpromneft-Lubricants accept no liability for any damage or loss resulting from using the product in purposes other than it intended, from any failure to comply with the recommendations or from hazards inherent in the nature of the material. If you require any further information please consult