

Gazpromneft Premium JK 0W-20, 5W-20, 5W-30



Engine oils



Fully synthetic base oil



All-season,
0W-20, 5W-20,
5W-30



Gasoline engines



Asian vehicles



Special polymer molecules

Gazpromneft Premium JK are all-season fully-synthetic energy conserving engine oils. Designed for protection of high-performance gasoline engines of modern Japanese, Korean, American vehicles, operating in wide working conditions range.

Advantages

- Fuel economy due to optimal anti-friction properties
- Engine performance preservation provided by combination of modern additive package and synthetic base oils
- Confident engine cold start secured by high oil pumpability at temperatures below zero
- Engine parts cleanliness thanks to effective deposits control and improved detergency properties
- Special polymer molecules ensure strong oil film and stable engine lubrication

Application



- Passenger cars, light off-road trucks, SUVs, vans and LCVs, produced by Japanese, Korean and other manufacturers
- Gasoline engines, requiring energy-conserving SAE 0W-20, 5W-20, 5W-30 viscosity grades, API SP/ILSAC GF-6A and lower tier products
- Toyota, Lexus, Subaru, Mazda, Suzuki, Mitsubishi, Honda, Kia and other OEMs gasoline engines requiring ILSAC GF-6A, GF-5, GF-4, GF-3 according to OEM requirements

Specification	Gazpromneft Premium JK		
	0W-20	5W-20	5W-30
API SP, SN	✓	✓	✓
ILSAC GF-6A, GF-5	✓	✓	✓
Chrysler MS-6395	✓	✓	✓
Fiat 9.55535-CR1	✓	✓	✓
Ford WSS-M2C-929-A			✓

Typical characteristics

Properties	Method	Gazpromneft Premium JK		
		0W-20	5W-20	5W-30
Kinematic Viscosity, mm ² /s at 40 °C at 100 °C	ASTM D 445	44,6 8,4	50,0 8,5	62,7 10,5
Viscosity Index	ASTM D 2270	168	147	158
Flash Point (COC), °C	ASTM D 92	239	240	237
Pour Point, °C	GOST 20287	-46	-48	-47
Total Base Number, mg KOH/g	ASTM D 2896	7,8	9,1	9,2
Density at 20 °C, kg/m ³	ASTM D 4052	847	850	850

The company's management system is certified in accordance with international standards:

ISO 9001



ISO 14001



ISO 45001

