



Gazpromneft Premium N 20W-50

Passenger Vehicle Engine Oils



Engine oil



Gasoline and diesel engines



Multigrade



Advanced polymers



Engine cleanliness



Semisynthetic

Gazpromneft Premium N 20W-50 is high performance engine oil providing high level of protection and performance under variety of operation conditions. It is formulated with high quality base oils and selected additives delivering long engine life for many types and ages of vehicles protecting against sludge and wear. Gazpromneft Premium N 20W-50 has a higher viscosity that help to provide full engine protection under higher operating speeds, temperatures, and other adverse conditions.

Applications



• Turbo-charged and direct injection high performance engines

• Gasoline and diesel engines without diesel particulate filters (DPF) requiring API SN or API CF performance

• Passenger cars, SUV's, light trucks and vans

Features	Advantages and Potential Benefits	
Multi-purpose application	High quality formulation suitable for a wide range of vehicles requiring premium quality product	
Wear protection	Strong oil film provides protection against wear under all operating conditions for long engine life	
Improved thermal and oxidation stability	Helps to resist oil aging allowing extended drain interval protection	
Deposit control	Prevents forming of sludge and harmful deposits through the use of advanced detergent additives for engine cleanliness	
Stay-in-grade	Keeps protective oil film during the whole drain interval and maintains viscosity grade	

Recommendations

API SN

API CF

ISO 9001

ISO 14001

♥ ISO/TS 16949

OHSAS 18001

CERTIFIED

GAZPROMNEFT – LUBRICANTS, LTD. 14/3, Krzhyzhanovskogo Street, Moscow, 117218 Russia Tel: +7 (495) 642-99-69 Fax:+7 (495) 921-48-63 www.gazpromneft-oil.com While the information and figures given here are typical of current production and conform to specification, minor variations may occur. The information contained is subject to change without notice. Gazpromneft-Lubricants accept no liability for any damage or loss resulting from using the product in purposes other than it intended, from any failure to comply with the recommendations or from hazards inherent in the nature of the material. If you require any further information please consult our technical helpdesk. E-mail: <u>OilSupport@gazprom-neft.ru</u> 03/2020

Typical Characteristics

Properties	Method	Gazpromneft Premium N 20W-50
SAE Viscosity Grade	SAE J300	20W-50
Kinematic Viscosity @100°C, mm ² /s	ASTM D445	18,7
Viscosity Index	ASTM D2270	120
Flash Point (COC), °C	ASTM D92	235
Pour Point, °C	ASTM D97	-32
Total Base Number, mg KOH/g	ISO 6619	11,2
Density @15°C, kg/m ³	ASTM D4052	891

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.

Ø ISO 9001

ISO 14001

GAZPROMNEFT - LUBRICANTS, LTD. 14/3, Krzhyzhanovskogo Street, Moscow, 117218 Russia Tel: +7 (495) 642-99-69 Fax:+7 (495) 921-48-63 www.gazpromneft-oil.com

V ISO/TS 16949

OHSAS 18001

CERTIFIED

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. The information contained is subject to change without notice. Gazpromneft-Lubricants accept no liability for any damage or loss resulting from using the product in purposes other than it intended, from any failure to comply with the recommendations or from hazards inherent in the nature of the material. If you require any further information please consult our technical beloaded. For many further without notice acception of the material of the materi helpdesk. E-mail: OilSupport@gazprom-neft.ru 03/2020