

## Gazpromneft Premium L 5W-30, 5W-40, 10W-30, 10W-40, 15W-40, 20W-50



Engine oils



Semi-synthetic oils  
(SAE 5W-30, 5W-40,  
10W-30, 10W-40)



Mineral oils  
(SAE 15W-40,  
20W-50)



Gasoline and diesel  
engines



Multigrade  
(all-season) oils



Specialised  
polymeric  
molecules

Gazpromneft Premium L – a series of universal multigrade engine oils designed for maximum protection of gasoline and diesel engines of passenger cars working in various operating conditions. The oils provide engine cleanliness and high wear protection in accordance with the requirements of car manufacturers.

### Advantages

- Maintain cleanliness of engine components by preventing deposit formation and high detergent properties
- Reliable cold engine starting when using SAE 5W-30 and 5W-40 oils due to high pumpability at low temperatures.
- Can be used in a wide range of ambient temperatures due to the availability of different viscosity grades in the product line.
- Excellent engine protection due to specialized polymer molecules that maintain a durable oil film.

### Application



- Passenger cars, off-road vehicles, vans, and light trucks of European and other manufacturers
- Designed for gasoline and diesel engines (turbocharged and non-turbocharged) in a wide fleet of vehicles where API SL/CF performance level and lower is required.

Specifications	Gazpromneft Premium L					
	5W-40	5W-30	10W-40	10W-30	15W-40	20W-50
API SL	✓	✓	✓	✓	✓	✓
API CF	✓	✓		✓	✓	
PJSC AVTOVAZ	✓	✓	✓			

## Typical characteristics

Properties	Method	Gazpromneft Premium L					
		5W-40	5W-30	10W-40	10W-30	15W-40	20W-50
Kinematic Viscosity, mm <sup>2</sup> /s at 40 °C at 100 °C	ASTM D 445	88,1	70,8	98,3	81,3	112,4	178,0
	ASTM D 445	14,5	11,7	14,3	12,1	14,8	18,9
Viscosity index	ASTM D 2270	170	163	152	144	136	123
Flash point in open cup, °C	ASTM D 92	230	228	236	242	243	246
Pour point, °C	ASTM D 97	-44	-40	-43	-37	-35	-29
Total base number, mg KOH/g	GOST 11362	9,1	9,1	9,1	9,1	9,1	9,1
Density at 20 °C, kg/m <sup>3</sup>	ASTM D 4052	856	854	869	870	880	882
Sulphated ash	ASTM D 874	1,1	1,1	1,1	1,1	1,1	1,1

The company's management system is certified in accordance with international standards:

ISO 9001



ISO 14001



ISO 45001

