

Gazpromneft Ecogas 15W-40

Passenger Vehicle Engine Oils



Engine oil



Mineral



LPG fueled engines



Gasoline and diesel engines



High oxidation stability

Gazpromneft Ecogas 15W-40 is high quality mineral oil which has been developed to provide excellent protection of the LPG fueled engines under all operating conditions. Gazpromneft Ecogas 15W-40 formulated with the use of advanced additive system to provide protection against wear, corrosion, all types of deposits and oil thickening at all temperatures.

Applications



- Gas-fueled (natural gas and LPG) spark ignition engines where conventional passenger car motor oils are recommended
- Gasoline and diesel engines without diesel particulate filters (DPF) requiring oil with API SL/CF standards
- Passenger cars, light trucks and vans

Features	Advantages and Potential Benefits
Multi-purpose application	High quality formulation suitable for a wide range of vehicles
Wear protection	Strong oil film provides protection against wear under all operating conditions for long engine life
Good detergent and dispersant properties	Prevents forming of sludge and harmful deposits even under high temperature for long-term engine cleanliness
Thermal and oxidation stability	Resistance to oil degradation that contributes to filter blocking and sludge formation

Recommendations

- API SL/CF

Typical Characteristics

Properties	Method	Gazpromneft Ecogas 15W-40
SAE Viscosity Grade	SAE J300	15W-40
Kinematic Viscosity @40°C, mm²/s	ASTM D445	107,8
Kinematic Viscosity @100°C, mm²/s	ASTM D445	14,5
Viscosity Index	ASTM D2270	138
Flash Point (COC), °C	ASTM D92	235
Pour Point, °C	ASTM D97	-32
Total Base Number, mg KOH/g	ISO 6619	7,2
Density @15°C, kg/m³	ASTM D4052	880
Sulfated Ash, wt%	ASTM D874	1,1

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.



GAZPROMNEFT – LUBRICANTS, LTD.
14/3, Krzhizhanovskogo Street, Moscow, 117218 Russia
Tel: +7 (495) 642-99-69
Fax: +7 (495) 921-48-63
www.gazpromneft-oil.com



While the information and figures given here are typical of current production and conform to specification, minor variations may occur. The information contained is subject to change without notice. Gazpromneft-Lubricants accept no liability for any damage or loss resulting from using the product in purposes other than it intended, from any failure to comply with the recommendations or from hazards inherent in the nature of the material. If you require any further information please consult our technical helpdesk. E-mail: Techservice@gazprom-neft.ru 10/2022

